

Mold Greases

NanoCeramicGrease

Extreme Performance Lubricating Grease



- Extraordinary adhesion, remains on the surface even under extreme pressure and temperature
- Does not soften and run out of the application during use
- Operating temperatures up to 426°C
- Provides outstanding protection against rust and corrosion. Resists water, steam, acid, salt and most corrosive chemicals
- High load bearing properties
- High pressure and anti-wear protection
- NSF Food Grade Certified; chemically inert and environmentally friendly
- Super low coefficient of friction, lower than PTFE greases
- Does not contain PTFE, silicone, lead, chlorine, zinc, antimony, barium
- Color white

Part Number	Package Size	Container	Package Quantity	Shelf Life
NCG - 1	454 g	Tube	1	2 years
NCG - 12	454 g	Tube	Case (12)	2 years
NCG - 2	3,8 l	Tub	1	2 years
NCG - 3	19 l	Pail	1	2 years

Cera Lube Spray Grease

Ideal to penetrate into tight passages



- White lithium grease lubricant formulated to spray on evenly and set dry
- Operating temperature up to 343°C
- The ceramic reinforced PTFE additives provide superior adhesion in high wear applications
- Protects against rust and corrosion
- Does not breakdown or run off in high wear applications
- Excellent adhesive to all metal surfaces
- Low thermal expansion
- Resists moisture and outside contaminants
- Compatible with NanoCeramicGrease

Part Number	Package Size	Container	Package Quantity	Shelf Life
CL - 1	454 g	Can	1	2 years
CL - 12	454 g	Can	Case (12)	2 years